

. (B)

Page 1 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

VARIOL® Sauer

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Descaler

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

DREITURM GmbH

Postach 11 40

36392 Steinau an der Straße Tel.: +49 (0) 66 63 / 970 - 0 Fax: +49 (0) 66 63 / 970 - 490

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+1 872 5888271 (DTR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Eye Dam. 1 H318-Causes serious eye damage. Met. Corr. 1 H290-May be corrosive to metals.

Skin Corr. 1 H314-Causes severe skin burns and eye damage.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger



Page 2 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

H290-May be corrosive to metals. H314-Causes severe skin burns and eye damage.

P260-Do not breathe vapours or spray. P280-Wear protective gloves / protective clothing and eye protection / face protection. P301+P330+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.

Phosphoric acid Isotridecanol, ethoxylated

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a. **3 9 Mixtures**

Phosphoric acid	Substance for which an EU exposure limit value
	applies.
Registration number (REACH)	01-2119485924-24-XXXX
Index	015-011-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	231-633-2
CAS	7664-38-2
content %	10-<25
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Met. Corr. 1, H290
factors	Skin Corr. 1B, H314
	Eye Dam. 1, H318
Specific Concentration Limits and ATE	Skin Corr. 1B, H314: >=25 %
•	Skin Irrit. 2, H315: >=10 %
	Eye Dam. 1, H318: >=25 %
	Eye Irrit. 2, H319: >=10 %

Isotridecanol, ethoxylated	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	
CAS	69011-36-5
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-	Acute Tox. 4, H302
factors	Eye Dam. 1, H318
Specific Concentration Limits and ATE	Eye Dam. 1, H318: >10 %
	Eye Irrit. 2, H319: 1-10 %

2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol	
Registration number (REACH)	01-2119777867-13-XXXX
Index	
EINECS, ELINCS, NLP, REACH-IT List-No.	202-414-9
CAS	95-38-5
content %	0,01-<0,25



(B)

Page 3 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

Classification according to Regulation (EC) 1272/2008 (CLP), M-

factors

Acute Tox. 4, H302 Skin Corr. 1C, H314 Eye Dam. 1, H318

STOT RE 2, H373 (gastrointestinal tract, thymus) (oral)

Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=1)

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Cauterizations not treated lead to wounds difficult to heal.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.

Protect uninjured eye.

Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Corrosive burns on skin as well as mucous membrane possible.

Risk of serious damage to eyes.

Conjunctivitis

Corneal damage.

Danger of blindness.

Ingestion:

pain in the mouth and throat

stomach pain

Oesophageal perforation

Gastric perforation

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

There should be an eyewash station and safety shower located near the area of use.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:



- (B

Page 4 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

Oxides of carbon Oxides of phosphorus Toxic gases

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.

Ensure sufficient ventilation, remove sources of ignition.

Avoid dust formation with solid or powder products.

Leave the danger zone if possible, use existing emergency plans if necessary.

Keep non-essential personnel away.

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

Neutralising is possible (only from a specialist).

Flush residue using copious water.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.



Page 5 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

Do not use acid sensitive materials. Acid-resistant floor necessary. Store separately from alkalis.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Phosphoric acid	Content %:10- <25					
WEL-TWA: 1 mg/m3 (WEL, EU) WEL-STEL: 2 mg/m3 (WEL, EU) -						
Monitoring procedures:	 INSHT MTA/MA-019/A90 (Determination of inorganic acid a 	anions in air)					
- OSHA ID-111 (Phosphoric Acid in Workplace Atmospheres)							
	- OSHA ID-165SG (Acid Mist In Workplace Atmospheres) - 1	1985					
BMGV:	Other information:						

Phosphoric acid							
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note	
Consumer	Human - inhalation	Long term, local effects	DNEL	0,73	mg/m3		
Consumer	Human - inhalation	Short term, local effects	DNEL	2	mg/m3		
Consumer	Human - inhalation	Long term, systemic effects	DNEL	4,57	mg/m3		
Workers / employees	Human - inhalation	Long term, local effects	DNEL	2,92	mg/m3		
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	10,7	mg/m3		
Workers / employees	Human - inhalation	Long term, local effects	DNEL	1	mg/m3		

2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol								
Area of application	Exposure route / Environmental compartment	Effect on health	Descripto r	Value	Unit	Note		
	Environment - freshwater		PNEC	0	mg/l			
	Environment - marine		PNEC	0	mg/l			
	Environment - sewage treatment plant		PNEC	0,27	mg/l			
	Environment - sediment, freshwater		PNEC	0,376	mg/kg			
	Environment - sediment, marine		PNEC	0,038	mg/kg			
	Environment - soil		PNEC	0,075	mg/kg			
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	0,46	mg/m3			
Workers / employees Human - dermal		Long term, systemic effects	DNEL	0,06	mg/kg body weight/day			

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period)
EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States



(B)

Page 6 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision. (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

If applicable:

Face protection (EN 166).

Skin protection - Hand protection:

Use acid resistant protective gloves (EN ISO 374).

If applicable

Protective gloves made of natural rubber latex (EN ISO 374).

Protective gloves made of fluorocarbon rubber (EN ISO 374).

Protective PVC gloves (EN ISO 374).

Protective gloves made of chloroprene (EN ISO 374).

Protective gloves in butyl rubber (EN ISO 374).

Minimum layer thickness in mm:

0.5

Permeation time (penetration time) in minutes:

>480

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Protective hand cream recommended.

Skin protection - Other:

Acid-resistant protection clothing (EN 13034)

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

If applicable, filter P2 (EN 143), code colour white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable



Page 7 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Liquid Colour: Colourless Characteristic Odour:

Melting point/freezing point: There is no information available on this parameter.

Boiling point or initial boiling point and boiling range: There is no information available on this parameter.

There is no information available on this parameter. Flammability: Lower explosion limit: There is no information available on this parameter.

There is no information available on this parameter. Upper explosion limit:

Flash point: There is no information available on this parameter. Auto-ignition temperature: There is no information available on this parameter.

Decomposition temperature: There is no information available on this parameter. pH:

Kinematic viscosity: There is no information available on this parameter.

Solubility: Soluble Partition coefficient n-octanol/water (log value):

Does not apply to mixtures. There is no information available on this parameter. Vapour pressure:

Density and/or relative density: 1,148 g/ml

Relative vapour density: There is no information available on this parameter.

Particle characteristics: Does not apply to liquids.

9.2 Other information

Explosives: Product is not explosive.

Oxidising liquids:

SECTION 10: Stability and reactivity

10.1 Reactivity

Product corrodes metals.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Avoid contact with strong alkalis (exothermic reaction possible).

Avoid contact with certain metals e.g. aluminium (development of hydrogen gas possible).

10.4 Conditions to avoid

None known

10.5 Incompatible materials

Avoid contact with strong alkalis.

Avoid contact with certain metals e.g. aluminium.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008



Page 8 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014 Valid from: 01.11.2021

PDF print date: 01.11.2021

VARIOL® Sauer

Possibly more information on health effects, see Section 2.1 (classification).

VARIOL® Sauer	icaitii ciiccis,	SCC OCCION	2.1 (01033111001	011).		
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000		Organism	restilletilou	calculated value
	AIL	>2000	mg/kg			
Acute toxicity, by dermal						n.d.a.
route:						
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye						n.d.a.
damage/irritation:						
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						
Specific target organ toxicity -						n.d.a.
repeated exposure (STOT-						
RÉ):						
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2600	mg/kg	Rat		
Acute toxicity, by dermal	LD50	2740	mg/kg	Rabbit		
route:						
Acute toxicity, by inhalation:	LC50	1,689	mg/l/1h	Rabbit		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Corrosive
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit		Corrosive
damage/irritation:						
Respiratory or skin				Human being	(Patch-Test)	Not sensitizising
sensitisation:						
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation	
					Test)	
Carcinogenicity:						Negative
Reproductive toxicity:	NOAEL	370-410	mg/kg		OECD 414 (Prenatal	Not to be
					Developmental	expected
					Toxicity Study)	
Reproductive toxicity (Effects	NOAEL	>=500	mg/kg		OECD 422	Not to be
on fertility):					(Combined Repeated	expected
					Dose Tox. Study with	
					the	
					Reproduction/Develop	
					m. Tox. Screening	
					Test)	
Specific target organ toxicity -	NOAEL	250	mg/kg	Rat	OECD 422	
repeated exposure (STOT-					(Combined Repeated	
RE):					Dose Tox. Study with	
					the	
					Reproduction/Develop	
					m. Tox. Screening	
					Test)	



Page 9 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014 Valid from: 01.11.2021

PDF print date: 01.11.2021

VARIOL® Sauer

Symptoms:		respiratory
		distress,
		vomiting,
		coughing,
		collapse,
		cramps,
		mucous
		membrane
		irritation, shock

Isotridecanol, ethoxylated Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	500-2000	mg/kg	Rat	OECD 423 (Acute	
<i>3,</i> 3					Oral Toxicity - Acute	
					Toxic Class Method)	
Acute toxicity, by dermal	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
route:					Dermal Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye				Rabbit	(Draize-Test)	Risk of serious
damage/irritation:						damage to
						eyes.
Serious eye		>10	%		OECD 437 (Bovine	Eye Dam. 1
damage/irritation:					Corneal Opacity +	
					Permeability Test for	
					Identif. Ocular Corros.	
					+ Severe Irritants)	

2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	1265	mg/kg	Rat	OECD 401 (Acute	Analogous
					Oral Toxicity)	conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Corrosive,
					Dermal	Analogous
					Irritation/Corrosion)	conclusion
Serious eye				Rabbit	OECD 405 (Acute	Corrosive,
damage/irritation:					Eye	Analogous
-					Irritation/Corrosion)	conclusion
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin
sensitisation:					Sensitisation)	contact),
						Analogous
						conclusion
Germ cell mutagenicity:				Salmonella	OECD 471 (Bacterial	Negative,
				typhimurium	Reverse Mutation	Analogous
					Test)	conclusion
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro	Negative,
					Mammalian	Analogous
					Chromosome	conclusion
					Aberration Test)	
Specific target organ toxicity -				Rat	OECD 422	Target
repeated exposure (STOT-					(Combined Repeated	organ(s):
RE), oral:					Dose Tox. Study with	gastrointestinal
					the	tract, Target
					Reproduction/Develop	organ(s):
					m. Tox. Screening	thymus
					Test)	

11.2. Information on other hazards

VARIOL® Sauer						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



Page 10 of 15 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

Endocrine disrupting properties:	Does not apply to mixtures.
Other information:	No other relevant information available on adverse effects on health.

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification). Neutralisation possible.

Low pH-value can be harmful to water.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:			1 2000		J. g		n.d.a.
12.1. Toxicity to							n.d.a.
daphnia:							
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							The
degradability:							surfactant(s)
3							contained in
							this mixture
							complies(comp
							y) with the
							biodegradabili
							criteria as laid
							down in
							Regulation
							(EC)
							No.648/2004
							on detergents
							Data to suppo
							this assertion
							are held at the
							disposal of the
							competent
							authorities of
							the Member
							States and wil
							be made
							available to
							them, at their
							direct request
							or at the
							request of a
							detergent
							manufacturer.
12.3. Bioaccumulative							n.d.a.
ootential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Endocrine							Does not appl
disrupting properties:							to mixtures.



Page 11 of 15
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014 Valid from: 01.11.2021

PDF print date: 01.11.2021 VARIOL® Sauer

12.7. Other adverse effects:		No information available on other adverse effects on the environment.
Other information:		DOC- elimination degree(complex ing organic substance)>= 80%/28d: n.a.

Phosphoric acid							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	3,0 - 3,25	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.3. Bioaccumulative potential:	Log Pow		-0,77				calculated value
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		270	mg/l	activated sludge		

Isotridecanol, ethoxylated							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>1	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	References
12.1. Toxicity to fish:	LC50	96h	>1-10	mg/l	Leuciscus idus	1 001)	
12.1. Toxicity to daphnia:	EC50	48h	>1-10	mg/l			
12.1. Toxicity to algae:	EC50	72h	>1-10	mg/l			
12.2. Persistence and degradability:		28d	>60	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
Toxicity to bacteria:	EC10	17h	>10000	mg/l	activated sludge	·	
Other information:	COD		2100	mg/g			

2-(2-heptadec-8-enyl-2-imidazolin-1-yl)ethanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to algae:	EC10	72h	0,014	mg/l	Desmodesmus	OECD 201	Analogous
					subspicatus	(Alga, Growth	conclusion
						Inhibition Test)	
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance
12.1. Toxicity to fish:	LC50	96h	0,3	mg/l	Brachydanio rerio	OECD 203	
						(Fish, Acute	
						Toxicity Test)	
	•		•	•	•		



-GB

Page 12 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

12.1. Toxicity to daphnia:	EC50	48h	0,163	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EC50	72h	0,03	mg/l	Desmodesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	1	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not biodegradable

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

06 01 04 phosphoric and phosphorous acid

20 01 29 detergents containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number or ID number: 1805

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 1805 PHOSPHORIC ACID, SOLUTION

14.3. Transport hazard class(es):
14.4. Packing group:
Classification code:
LQ:

8

C1

C1

14.5. Environmental hazards:

Not applicable

Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name: PHOSPHORIC ACID SOLUTION

14.3. Transport hazard class(es):

14.4. Packing group:

III

Ems:

EmS: F-A, S-B Marine Pollutant: n.a

14.5. Environmental hazards: Not applicable

Transport by air (IATA) 14.2. UN proper shipping name:







Page 13 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

Phosphoric acid, solution

14.3. Transport hazard class(es):

8

14.4. Packing group:

Ш

14.5. Environmental hazards:

Not applicable

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC):

0 %

National rules/regulation for the compliance with maximum quantities with regard to phosphates and or phosphorous compounds must be observed and complied with.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

1-16

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation	Evaluation method used		
(EC) No. 1272/2008 (CLP)			
Eye Dam. 1, H318	Classification based on the pH value.		
Met. Corr. 1, H290	Classification based on test data.		
Skin Corr. 1, H314	Classification based on the pH value.		

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Eye Dam. — Serious eye damage





. (B)

Page 14 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

Met. Corr. — Substance or mixture corrosive to metals

Skin Corr. — Skin corrosion Acute Tox. — Acute toxicity - oral

STOT RE — Specific target organ toxicity - repeated exposure Aquatic Acute — Hazardous to the aquatic environment - acute Aquatic Chronic — Hazardous to the aquatic environment - chronic

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.

Guidelines for the preparation of safety data sheets as amended (ECHA).

Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).

Safety data sheets for the constituent substances.

ECHA Homepage - Information about chemicals.

GESTIS Substance Database (Germany).

German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).

EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.

National Lists of Occupational Exposure Limits for each country as amended.

Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

DOC Dissolved organic carbon

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)

EC European Community

ECHA European Chemicals Agency

ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

ErCx, E μ Cx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals



- (B

Page 15 of 15

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 23.06.2021 / 0014

Valid from: 01.11.2021 PDF print date: 01.11.2021

VARIOL® Sauer

GWP Global warming potential

Koc Adsorption coefficient of organic carbon in the soil

Kow octanol-water partition coefficient

IARC International Agency for Research on Cancer

IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLIDInternational Uniform Chemical Information Database

IUPAC International Union for Pure Applied Chemistry

LC50 Lethal Concentration to 50 % of a test population

LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)

Log Koc Logarithm of adsorption coefficient of organic carbon in the soil

Log Kow, Log Pow Logarithm of octanol-water partition coefficient

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

NIOSH National Institute for Occupational Safety and Health (USA)

NLP No-longer-Polymer

NOEC, NOEL No Observed Effect Concentration/Level

OECD Organisation for Economic Co-operation and Development

org. organic

OSHA Occupational Safety and Health Administration (USA)

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.