

Method card

BUZIL-WERK Wagner GmbH & Co. KG

CORRIDOR® BASIC S 720

Application area: Floor / coating				
Dilution	Undiluted (1:1 with water)			
Suitable for	Pore filler / primer; Porous floor coverings; Absorbent floor coverings	Not suitable for	Textile surfaces; Sealed floor coverings such as PVC, vinyl or synthetic resin	
Application	Water-resistant floor coverings; Linoleum (undiluted); Concrete (first coat, dilute 1:1 with water); Screed (first coat, dilute 1:1 with water); Only prime terracotta once (first coat, dilute 1:1 with water)			
Λ	Issue / Failture / Requirement	Solving Issue		
	 Poor penetration 	 Covering too porous, apply another layer 		
Shooting	 Foaming with "craters" as a result after drying Powdering off when used Severe marking when used 	 Covering too rough, spread more slowly when applying Before applying, do not let the covering dry / deep clean again Intensive cleaning with Maradin HC 43, 		
Before initial use:		Indumaster® Strong IR 45, Indumaster® Forte IR 42		
Test material compatibility!	 Grey / mat appearance of sur- face due to hard water Damage on surface (discolorati- 	 Clean periodically with 0 Tens Azid G 501 Check material's chemical and water resistance 		



Method card

BUZIL-WERK Wagner GmbH & Co. KG

ALTERNATIVE PRODUCT | CORRIDOR® BASIC S 720

Application area: Floor / coating	рн 8	
Alternative Product	Differentiation	Application
Corridor® Glorin S 734	All-purpose dispersion, free of metallic salts	Glossy floor coating
Corridor® Jewel S 741	High-performance dispersion, free of metallic salts	Glossy floor coating
Planta® Multi Gloss P 320	Ecological dispersion, free of metallic salts	Glossy floor coating with good penetration