

Method card

BUZIL-WERK Wagner GmbH & Co. KG

POLYBUZ® T 201

Application area: Floor					
Dilution		50 ml / 10 l water 50 - 150 ml / 10 l water			
Suitable	for	Daily routine cleaning; Cleaning machines; Shiny surfaces	Not suitable for	Unsealed wooden surfaces; Textile surfaces	
Applicati	ion	Water resistant floor coverings; Sealed parquet; Laminate; Granit; Porcelain stoneware tiles; Ceramic wall and floor tiles; Shiny artificial and natural stones			
Trouble Shooting		Issue / Failture / Requirement	Solving Issue		
		 Leaves streaks; film on surface; too much foam in dilution Low; weak cleaning effect No cleaning effect 	 Adjust product dilution Select alkaline intensive cleaner i.e. Aktiv G 433, Maradin HC 43 Select problem solver i.e. Buz[®] Point 		
Before initia use: Test materia compatibilit	al	 No cleaning enect Leaves spots on shiny impregnated surfaces Damage on surface (discoloration, material swelling, etc.) Grey; mat appearance of surface due to hard water 	 G 502, Radana HC 42 Select ultra-wetting cleaner i.e. Roca Wipe R 300 Check material's chemical & water resistance Clean periodicly with 0 Tens Azid G 501 		



Method card

BUZIL-WERK Wagner GmbH & Co. KG

ALTERNATIVE PRODUCT | POLYBUZ® T 201

Differentiation	Application
Tested acc. to FMPA DIN 18032/2	Daily routine cleaning, sport floors
Alcohol free product	Daily routine floor cleaning
Cleaner for PUR coated surfaces	Daily routine floor cleaning
	Tested acc. to FMPA DIN 18032/2 Alcohol free product

© BUZIL-WERK Wagner GmbH & Co. KG | Fraunhoferstr. 17 | 87700 Memmingen | www.buzil.de