according to Regulation (EC) No 1907/2006



Corridor® Power Stripper

Revision date: 28.04.2023 S708 Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Corridor® Power Stripper

UFI: 1JR0-U0XC-M00V-28S2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

EuPCS: PC-CLN-13.3 Floor strippers Process categories [PROC]: 8, 10 Restricted to professional users.

1.3. Details of the supplier of the safety data sheet

Company name: BUZIL-WERK Wagner GmbH & Co. KG

Street: Fraunhofer Str. 17
Place: D-87700 Memmingen
Telephone: +49 (0) 8331 930-6

elephone: +49 (0) 8331 930-6 Telefax: +49 (0) 8331 930-880

e-mail: info@buzil.de
Contact person: info@buzil.de
Internet: www.buzil.com

1.4. Emergency telephone +49 (0) 8331 930-6 (08:00 - 16:00 h)

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Eye Dam. 1; H318

Full text of hazard statements: see SECTION 16.

The product does not support combustion. It therefore needs not to be classified as flammable despite a flash point below 60 °C.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Alkyl polyethoxylate

Signal word: Danger

Pictograms:



Hazard statements

H318 Causes serious eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

according to Regulation (EC) No 1907/2006



Corridor® Power Stripper

Revision date: 28.04.2023 S708 Page 2 of 11

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
_	EC No	Index No	REACH No		
	Classification (Regulation (EC) No	1272/2008)	·		
112-34-5	2-(2-Butoxyethoxy)ethanol, Diethy	lene glycol monobutyl ethe	r	35 - < 40 %	
	203-961-6	603-096-00-8	01-2119475104-44		
	Eye Irrit. 2; H319	•	•		
100-51-6	Benzyl alcohol			10 - < 15 %	
	202-859-9	603-057-00-5	01-2119492630-38		
	Acute Tox. 4, Acute Tox. 4; H332				
64-17-5	Ethanol	10 - < 15 %			
	200-578-6	603-002-00-5	01-2119457610-43		
	Flam. Liq. 2, Eye Irrit. 2; H225 H3				
78330-21-9	Alkyl polyethoxylate			1 - < 5 %	
	934-084-3				
	Eye Dam. 1, Aquatic Chronic 3; H				
15763-76-5	Sodium cumene sulfonate	1 - < 5 %			
	239-854-6		01-2119489411-37		
	Eye Irrit. 2; H319				

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc.	Limits, M-factors and ATE	
112-34-5	203-961-6	2-(2-Butoxyethoxy)ethanol, Diethylene glycol monobutyl ether	35 - < 40 %
	inhalation: LC5	50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	
100-51-6	202-859-9	Benzyl alcohol	10 - < 15 %
		E = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = al: LD50 = 1230 mg/kg	
64-17-5	200-578-6	Ethanol	10 - < 15 %
	inhalation: LC5 Eye Irrit. 2; H31	50 = >20 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg l9: >= 50 - 100	
78330-21-9	934-084-3	Alkyl polyethoxylate	1 - < 5 %
	inhalation: LC5 mg/kg	50 = > 5 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2000	
15763-76-5	239-854-6	Sodium cumene sulfonate	1 - < 5 %
	I	50 = >20 mg/l (vapours); inhalation: LC50 = >5 mg/l (dusts or mists); dermal: mg/kg; oral: LD50 = >7000 mg/kg	

Labelling for contents according to Regulation (EC) No 648/2004

< 5 % non-ionic surfactants, perfumes (Benzyl alcohol).

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated, saturated clothing immediately.

according to Regulation (EC) No 1907/2006



Corridor® Power Stripper

Revision date: 28.04.2023 S708 Page 3 of 11

After inhalation

Provide fresh air

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After indestion

Rinse mouth immediately and drink plenty of water.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet

alcohol resistant foam

Carbon dioxide

Extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products:

Carbon dioxide

Carbon monoxide

5.3. Advice for firefighters

Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Use personal protection equipment.

Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Ventilate affected area.

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

according to Regulation (EC) No 1907/2006



Corridor® Power Stripper

Revision date: 28.04.2023 S708 Page 4 of 11

For cleaning up

Treat the recovered material as prescribed in the section on waste disposal.

Other information

Collect in closed and suitable containers for disposal.

Ventilate affected area.

6.4. Reference to other sections

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with skin, eves and clothes.

Do not mix with other chemicals.

Use personal protection equipment.

When using do not eat, drink or smoke.

Use only in well-ventilated areas.

Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

No special fire protection measures are necessary.

Advice on general occupational hygiene

Take off contaminated clothing.

Wash hands before breaks and after work.

When using do not eat, drink or smoke.

Further information on handling

No further relevant information available.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed.

Hints on joint storage

No special measures are necessary.

Further information on storage conditions

No further relevant information available.

7.3. Specific end use(s)

Cleaning agent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m³	fib/cm³	Category	Origin
112-34-5	2-(2-Butoxyethoxy)ethanol	10	67.5		TWA (8 h)	
		15	101.2		STEL (15 min)	

according to Regulation (EC) No 1907/2006



Corridor® Power Stripper

Revision date: 28.04.2023 S708 Page 5 of 11

DNEL/DMEL values

CAS No	Name of agent					
DNEL type	Hame of agont	Exposure route	Effect	Value		
15763-76-5	Sodium cumene sulfonate					
Worker DNEL	, long-term	dermal	systemic	7,6 mg/kg bw/day		
Worker DNEL, long-term		inhalation	systemic	53,6 mg/m³		
Consumer DNEL, long-term		dermal	systemic	3,8 mg/kg bw/day		
Consumer DNEL, long-term		inhalation	systemic	13,2 mg/m³		
Consumer DNEL, long-term		oral	systemic	3,8 mg/kg bw/day		

PNEC values

CAS No	Name of agent				
Environmental compartment Value		Value			
15763-76-5 Sodium cumene sulfonate					
Micro-organisms in sewage treatment plants (STP)					

Additional advice on limit values

No information available.

8.2. Exposure controls





Appropriate engineering controls

No information available.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection. (EN 166)

Hand protection

Wear suitable gloves. (EN 374, Breakthrough time: >10 min.)

Suitable material: NBR (Nitrile rubber).

Thickness of the glove material >= 0,1 mm

A survey of suitable brands with detailed information on breakthrough times is available upon request.

Diluted ready-to-use solutions <=1%:

Protective gloves may be waived, if equivalent measures allowing for an increased skin stress because of wet work are implemented (e. g. application of suitable skin protecting creams).

Skin protection

Wear suitable work clothing.

Respiratory protection

Use only in well-ventilated areas.

In case of inadequate ventilation wear respiratory protection. (DIN EN 14387, A 1)

Thermal hazards

No further relevant information available.

Environmental exposure controls

Section 6: Accidental Release Measures

according to Regulation (EC) No 1907/2006



Corridor® Power Stripper

S708 Revision date: 28.04.2023 Page 6 of 11

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: colourless - light yellow Odour: Perfumes, fragrances

Test method

Melting point/freezing point: approx. 0 °C Boiling point or initial boiling point and approx. 100 °C

boiling range:

Flammability: not applicable Lower explosion limits: not determined Upper explosion limits: not determined 47 °C Flash point: Auto-ignition temperature: not determined Decomposition temperature: not applicable pH-Value (at 20 °C): approx. 9,5 Viscosity / kinematic: not determined

(at 40 °C)

Water solubility: completely miscible

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not applicable Vapour pressure: not determined Density (at 20 °C): 1,00 g/cm³ Relative density: not determined Relative vapour density: not determined Particle characteristics: not relevant

9.2. Other information

Information with regard to physical hazard classes

Sustaining combustion: Not sustaining combustion

Other safety characteristics

Viscosity / dynamic: < 10 mPa·s (50 1/s)

(at 25 °C)

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

The product is stable under storage at normal ambient temperatures.

10.5. Incompatible materials

No information available.

according to Regulation (EC) No 1907/2006



Corridor® Power Stripper

Revision date: 28.04.2023 S708 Page 7 of 11

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
112-34-5	2-(2-Butoxyethoxy)ethanol, Diethylene glycol monobutyl ether							
	oral	LD50 mg/kg	>2000	Rat	ATE			
	dermal	LD50 mg/kg	>2000	Rat	ATE			
	inhalation vapour	LC50	>20 mg/l	Rat	ATE			
100-51-6	Benzyl alcohol							
	oral	LD50 mg/kg	1230	Rat	GESTIS			
	dermal	LD50 mg/kg	2000	Rabbit				
	inhalation vapour	ATE	11 mg/l					
	inhalation dust/mist	ATE	1,5 mg/l					
64-17-5	Ethanol							
	oral	LD50 mg/kg	>2000	Rat	ATE			
	dermal	LD50 mg/kg	>2000	Rat	ATE			
	inhalation (4 h) vapour	LC50	>20 mg/l	Rat	ATE			
78330-21-9	Alkyl polyethoxylate							
	oral	LD50 mg/kg	> 2000	Rat		OECD 401		
	dermal	LD50 mg/kg	> 2000	Rat	ATE			
	inhalation dust/mist	LC50	> 5 mg/l	Rat	ATE			
15763-76-5	Sodium cumene sulfona	te						
	oral	LD50 mg/kg	>7000	Rat				
	dermal	LD50 mg/kg	>2000	Rabbit				
	inhalation vapour	LC50	>20 mg/l	Rat	ATE			
	inhalation dust/mist	LC50	>5 mg/l	Rat	ATE			

Irritation and corrosivity

Causes serious eye damage.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

according to Regulation (EC) No 1907/2006



Corridor® Power Stripper

Revision date: 28.04.2023 S708 Page 8 of 11

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Other information

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method	
112-34-5	2-(2-Butoxyethoxy)ethanol, Diethylene glycol monobutyl ether							
	Acute fish toxicity	LC50 mg/l	2780	96 h	Pimephales promelas (fathead minnow)			
	Acute algae toxicity	ErC50 mg/l	> 100		Scenedesmus subspicatus			
	Acute crustacea toxicity	EC50 mg/l	4950	48 h	Daphnia magna (Big water flea)			
100-51-6	Benzyl alcohol							
	Acute fish toxicity	LC50	460 mg/l	96 h	Pimephales promelas (fathead minnow)			
	Acute algae toxicity	ErC50	640 mg/l	96 h	Scenedesmus quadricauda			
64-17-5	Ethanol							
	Acute fish toxicity	LC50 mg/l	>1000	96 h				
	Acute algae toxicity	ErC50 mg/l	>100					
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna	IUCLID		
78330-21-9	Alkyl polyethoxylate							
	Acute fish toxicity	LC50 mg/l	1-10	96 h	Danio rerio (zebrafish)		OECD 203	
	Acute crustacea toxicity	EC50	0,7 mg/l	48 h	Daphnia magna (Big water flea)			
	Acute bacteria toxicity	(EC50 mg/l)	> 1000					
15763-76-5	Sodium cumene sulfonate	Sodium cumene sulfonate						
	Acute fish toxicity	LC50 mg/l	>1000	96 h				
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna (Big water flea)			
	Algae toxicity	NOEC	31 mg/l	4 d				

12.2. Persistence and degradability

The surfactants contained in this mixture comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.



according to Regulation (EC) No 1907/2006

Corridor® Power Stripper

Revision date: 28.04.2023 S708 Page 9 of 11

CAS No	Chemical name						
	Method	Value	d	Source			
	Evaluation	-	-				
112-34-5	2-(2-Butoxyethoxy)ethanol, Diethylene glycol monobutyl	ether					
	OECD 301	>60%	28				
	Readily biodegradable (according to OECD criteria).						
100-51-6	Benzyl alcohol						
	OECD 301	>60%	28				
	Readily biodegradable (according to OECD criteria).						
64-17-5	Ethanol						
	OECD 301	>60%	28				
	Readily biodegradable (according to OECD criteria).						
78330-21-9	Alkyl polyethoxylate						
	OECD 301F	> 60%	28				
	Readily biodegradable (according to OECD criteria).						
15763-76-5	Sodium cumene sulfonate						
	OECD 301B/ ISO 9439/ EEC 92/69/V, C.4-C	>60%	28				
	Readily biodegradable (according to OECD criteria).						

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-34-5	2-(2-Butoxyethoxy)ethanol, Diethylene glycol monobutyl ether	0,56
100-51-6	Benzyl alcohol	1,05
64-17-5	Ethanol	-0,31
15763-76-5	Sodium cumene sulfonate	-1,1

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Delivery to an approved waste disposal company.

List of Wastes Code - residues/unused products

070601 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the MFSU of fats, grease,

soaps, detergents, disinfectants and cosmetics; aqueous washing liquids and mother liquors;

hazardous waste

List of Wastes Code - contaminated packaging

according to Regulation (EC) No 1907/2006



Corridor® Power Stripper

Revision date: 28.04.2023 S708 Page 10 of 11

150102 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); plastic packaging

Contaminated packaging

Non-contaminated packages may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: No dangerous good in sense of these transport regulations.

Inland waterways transport (ADN)

14.1. UN number or ID number: No dangerous good in sense of these transport regulations.

Marine transport (IMDG)

14.1. UN number or ID number: No dangerous good in sense of these transport regulations.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: No dangerous good in sense of these transport regulations.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No special measures are necessary.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 40, Entry 55, Entry 75

2010/75/EU (VOC): 24,5 %

Additional information

Regulation (EC) No. 648/2004 [Detergents regulation]

National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,2,7,9,12,14,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%



according to Regulation (EC) No 1907/2006

Corridor® Power Stripper

Revision date: 28.04.2023 S708 Page 11 of 11

LD50: Lethal dose, 50%

Process categories according to ECHA guidance on information requirements and chemical safety assessment, chapter R.12:

PROC 1: Use in closed processes.

PROC 2: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 4: Chemical production where opportunity for exposure arises

PROC 7: Industrial spraying

PROC 8 (Transfer): Dilution of concentrated products, application of drain cleaners, dosage of textile washing agents.

PROC 9: Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC 10 (Roller application or brushing): Processing without large-scale spraying.

PROC 11 (Spraying outside industrial settings): Processing with large-scale spraying (e. g. high pressure cleaning, foam gun).

PROC 13: Treatment of articles by dipping and pouring

PROC 19 (Hand-mixing with intimate contact): Hand cleaning and disinfection

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.

Further Information

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]: 9 (1)

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)