

# Corridor® + Multi Stripper

P 937

Ecological universal stripper



## Area of application


- For water-resistant, alkali-sensitive elastic floor coverings such as linoleum, elastomer coverings and PVC
- Can be used on artificial and natural stone surfaces

## Product benefits/properties


- Eco-certified
- Developed for the removal of heavy deposits/polymer coatings
- Very good material compatibility
- Environmentally friendly formulation with good dirt and film-removing action
- Short exposure times
- Easy to remove from the surface
- Excellent for subsequent use with Corridor®+ Protect Glossy P 938

## Application and dosage

- Always use cold water.
- Spread cleaning solution on the floor, let it briefly take effect, clean thoroughly, vacuum the loosened dirt, remove residues.
- Consumption: 12,5 - 72 ml / per m<sup>2</sup>
- Depending on age, number of layer applications and type of coating.



- Apply fresh application solutions and consume them within 24 hours at the latest.



Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

## Remarks / Important information

- Not suitable for asphalt or bitumen coverings.
- Before processing, turn off heat sources (underfloor heating, heating, hot supply air).
- When used in the machine, the tanks should be cleaned and rinsed regularly.
- Changes or variations in colour of the product do not impact on the quality.
- **Safety:** Test material compatibility on a hidden area before application. For further information, please refer to the MSDS (Material Safety Data Sheet).
- **Storage:** Always keep containers closed. Store at room temperature in the original container.
- **Environmental:** Non-contaminated and emptied packages may be recycled.

## EU CLP - Regulation (EC) No 1272/2008



- Warning
- H319 Causes serious eye irritation.
- P305+P351+P338,P337+P313

## Technical data

- **Product colour:** colourless
- **Austrian Ecolabel:** UW 1126
- **GISBAU code:** GG 50
- **UFI code:** MKT0-00GV-Y00R-YFRM

## Sales units

- 1 x 5 l canister P937-0005