

Corridor® + Protect Glossy

P 938

Ecological dispersion, glossy



Area of application


- Suitable for use in hospitals, homes and areas where disinfectants are used
- For all elastic coatable (also residual moisture) and water-resistant floor coverings such as linoleum, PVC and elastomer coverings
- Coatable PUR-modified coverings
- Can also be used on natural and artificial stone

Product benefits/properties

- Eco-certified
- Resistant environmentally friendly formulation
- Free of metal salt
- Very good filling properties and good flow
- Surface disinfectant-resistant
- Polishable with the high-speed machine
- Durable appearance and high gloss
- Slip-resistant according to DIN 51131
- Suitable for coating repair
- Excellent for use with Corridor®+ Multi Stripper P 937
- Good adhesion even on floors that are only superficially dry

Application and dosage

- Apply undiluted a thin layer in 2 – 3 layers evenly on a thoroughly cleaned, neutralized and dry floor covering.
- Each layer must dry completely.
- Consumption: 25 - 35 ml /



Remark: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

Remarks / Important information

- Protect from frost.
- Avoid direct sunlight.
- Before processing, turn off heat sources (underfloor heating, heating, hot supply air).
- A single, temporary exposure on the surface without mechanics, to commercially available disinfectants (max. 15 Minutes of continuous stress) is tested and does not cause any damage to the coating surface.
- Changes or variations in colour of the product do not impact on the quality.
- **Safety:** Test material compatibility on a hidden area before application. For further information, please refer to the MSDS (Material Safety Data Sheet).
- **Storage:** Always keep containers closed. Store at room temperature in the original container.
- **Environmental:** Non-contaminated and emptied packages may be recycled.

EU CLP - Regulation (EC) No 1272/2008

The mixture is classified as not hazardous according to the above-mentioned regulation.

- EUH208 Contains 1,2-benzisothiazol-3(2H)-one, Methylchloroisothiazolinone, 2-methylisothiazol-3(2H)-one, 2-octyl-2H-isothiazol-3-one. May produce an allergic reaction.
- EUH210 Safety data sheet available on request.
- P280,P302+P352

Technical data

- **Product colour:** white
- **Austrian Ecolabel:** UW 1126
- **GISBAU code:** GE 10
- **UFI code:** QPT0-H069-9007-MTAP

Sales units

- 1 x 5 l canister P938-0005