




# INDUMASTER® OFFENSIVE IR 47

Intensive industrial cleaner, highly alkaline



### Fields of application

- For use in workshops and industrial applications
- Alkali-resistant floors and surfaces
- Epoxy resin coverings
- Tiles
- Ceramic and screed flooring

### Product advantages/properties

- Breaks down dirt
- Dissolves the stubbornest of encrustations
- Removes heavy rust, oily and greasy soil
- High dispersing properties
- Foam-inhibited
- Suitable for use with cleaner machine or with high-pressure cleaning machine

Technical data	
pH-Value	13,5
Product colour	yellow-orange
Container*	10 l canister 200 l drum

\* Please note: Some products may not be available in all territories. Please talk to your customer service representative.





## INDUSTRIAL CLEANER

Intensive cleaner

# INDUMASTER® OFFENSIVE IR 47

Intensive industrial cleaner, highly alkaline

### Application and dosage



Daily routine cleaning:  
100 - 200 ml / 10 l water



Intensive cleaning:  
200 - 500 ml / 10 l water



Machine cleaning:  
100 ml / 10 l water



Basic cleaning:  
1000 ml / 10 l water



High-pressure cleaning:  
1:5 to 1:10 with water

### Note

Always use cold water.

Do not mix with other cleaning agents. When being used in the automat, the tanks should be regularly cleaned and rinsed. Changes or variations in colour of the product do not impact on the quality.

### Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

For further safety precautions, please refer to the safety data sheet for Indumaster® Offensive IR 47 at [www.buzil.com](http://www.buzil.com).

GISBAU code: GG 90

Article number\*:

IR47-0010

IR47-0200

\* Please note: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

Date 20.10.2020

BUZIL-WERK Wagner GmbH & Co. KG

Fraunhoferstraße 17 . D-87700 Memmingen T +49 8331 930-6 . F +49 8331 930-880 . E-mail: [info@buzil.de](mailto:info@buzil.de) . [www.buzil.com](http://www.buzil.com)