



TOTAL G 424

Basic cleaner, highly alkaline



Fields of application

- Alkali-resistant and water-resistant hard floor covering such as PVC, stone (unpolished), brick slabs and earthenware slabs

Product advantages/properties

- Very good film-removing action
- Dissolves stubborn dirt
- For application in cleaning machines
- Foam-inhibited
- Highly alkaline
- Very good wetting properties
- With pleasant fragrance

| Technical data | |
|----------------|---------------|
| pH-Value | 14 |
| Product colour | yellow |
| Container* | 10 l canister |

* Please note: Some products may not be available in all territories. Please talk to your customer service representative.





TOTAL G 424

Basic cleaner, highly alkaline

Application and dosage



1 - 2,5 l : 10 l water

Spread solution evenly over the floor and allow approx. 10 min. contact time. Do not allow to dry. Then carry out basic cleaning with a single-disk machine or scrubbing dryer fitted with an appropriate pad.



Remove dirt solution with a wet vacuum cleaner. Then rinse the floor thoroughly with plenty of clean water.

Note

Always use cold water.

Check covering for colour fastness before application.

Not suitable for floors susceptible to alkalis, such as linoleum, rubber, open pore wood, cork and calciferous stone (e.g. marble and terrazzo).

When being used in the automat, the tanks should be regularly cleaned and rinsed. Changes or variations in colour of the product do not impact on the quality.

Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

For further safety precautions, please refer to the safety data sheet for Total G 424 at www.buzil.com.

GISBAU code: GG 80

Article number*:

G424-0010

* Please note: Some products may not be available in all territories. Please talk to your customer service representative.

The data in our product information sheets are based on our experience and careful investigations, and correspond to our present state of knowledge. We are, however, not able to examine and influence in detail the varying conditions for usage and materials, and those at premises where products are to be used. For this reason, we can only provide general information on usage. The quality of the work depends on expert assessment of the premises where products are to be used and how they are in fact employed by the user. In the case of doubt, the latter is obliged at all times to test the compatibility of the material to be treated with the Buzil product on an inconspicuous area or to obtain relevant advice on application technology. Liability for incomplete or incorrect data in our product information sheets shall only be assumed in cases of negligence caused by gross negligence or intent; any claims arising from the Product Liability Act shall remain unaffected. All previous product information shall lose its validity through the above listed product information.

Date 20.10.2020